


SAE Executive Standards Committee Rules provide that: " This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

REV. A			FEDERAL SUPPLY CLASS
AS1723™	RATIONALE THIS TECHNICAL REPORT IS BEING STABILIZED BECAUSE IT COVERS TECHNOLOGY, PRODUCTS, OR PROCESSES WHICH ARE MATURE AND NOT LIKELY TO CHANGE IN THE FORESEEABLE FUTURE. STABILIZED NOTICE THIS DOCUMENT HAS BEEN DECLARED "STABILIZED" BY SAE G-3, AEROSPACE COUPLINGS, FITTINGS, HOSE, TUBING ASSEMBLIES COMMITTEE AND WILL NO LONGER BE SUBJECTED TO PERIODIC REVIEWS FOR CURRENCY. USERS ARE RESPONSIBLE FOR VERIFYING REFERENCES AND CONTINUED SUITABILITY OF TECHNICAL REQUIREMENTS. NEWER TECHNOLOGY MAY EXIST.		
		For more information on this standard, visit https://www.sae.org/standards/content/AS1723A/	THIRD ANGLE PROJECTION 
CUSTODIAN: G-3/G-3A		PROCUREMENT SPECIFICATION:	
	AEROSPACE STANDARD HOSE, POLYTETRAFLUOROETHYLENE (TFE), HIGH TEMPERATURE AND MEDIUM PRESSURE (1500 PSIG) WITH INTEGRAL SILICONE COMPOSITE FIRE PROTECTION		AS1723™ REV. A

SAENORM.COM : Click to view the full PDF of as1723a

ISSUED 1982-10 REAFFIRMED 2013-01 STABILIZED 2024-09




TABLE I A - DIMENSIONS AND WEIGHT

HOSE SIZE (REF)	ID INSIDE DIA TUBE-INCH		WBOD OUTSIDE DIA BRAIDED-INCH		OD OUTSIDE DIA COVER-INCH		HOSE WEIGHT LBS/IN
	MIN	MAX	MIN	MAX	MIN	MAX	
-4	.173	.203	.304	.343	.600	.650	.018
-5	.235	.265	.367	.406	.660	.710	.020
-6	.298	.328	.430	.469	.720	.770	.023
-8	.391	.421	.546	.585	.850	.900	.030
-10	.485	.515	.641	.687	.945	1.005	.037
-12	.615	.645	.766	.812	1.075	1.135	.045
-16	.851	.906	1.078	1.140	1.395	1.455	.085
-20	1.101	1.156	1.328	1.390	1.650	1.710	.107
-24	1.344	1.406	1.637	1.707	1.965	2.025	.132

TABLE I B - DIMENSIONS AND WEIGHT (SI)

HOSE SIZE (REF)	ID INSIDE DIA TUBE-mm		WBOD OUTSIDE DIA BRAIDED-mm		OD OUTSIDE DIA COVER-mm		HOSE WEIGHT Kg/M
	MIN	MAX	MIN	MAX	MIN	MAX	
-4	4.39	5.16	7.72	8.71	15.24	16.51	.321
-5	5.97	6.73	9.32	10.31	16.76	18.03	.357
-6	7.57	8.33	10.92	11.91	18.29	19.56	.411
-8	9.93	10.69	13.87	14.86	21.59	22.86	.536
-10	12.32	13.08	16.28	17.45	24.00	25.53	.661
-12	15.62	16.38	19.46	20.62	27.31	28.83	.803
-16	21.62	23.01	27.38	28.96	35.43	36.96	1.518
-20	27.97	29.36	33.73	35.31	41.91	43.43	1.910
-24	34.14	35.71	41.58	43.36	49.91	51.44	2.357

TABLE II A - PERFORMANCE REQUIREMENTS (REF)

HOSE SIZE (REF)	OPERATING PRESSURE PSIG-MAX	PROOF PRESSURE PSIG-MIN	BURST PRESSURE-MIN		MIN BEND RAD INCH
			ROOM TEMP PSIG	400°F (204°C) PSIG	
-4	1500	3000	12000	7000	2.00
-5	1500	3000	10000	6500	2.00
-6	1500	3000	9000	6500	4.00
-8	1500	3000	8000	6000	4.62
-10	1500	3000	7000	5500	5.50
-12	1000	2000	5000	3500	6.50
-16	1250	2500	5000	3500	7.38
-20	1000	2000	4000	3000	11.00
-24	1000	2000	4000	3000	14.00

TABLE II B - PERFORMANCE REQUIREMENTS (SI) (REF)

HOSE SIZE (REF)	OPERATING PRESSURE kPa MAX	PROOF PRESSURE kPa MIN	BURST PRESSURE-MIN		MIN BEND RAD mm
			ROOM TEMP kPa	(204°C) 400°F kPa	
-4	10342	20684	82737	48263	50.8
-5	10342	20684	68948	44816	50.8
-6	10342	20684	62053	44816	101.6
-8	10342	20684	55158	41369	117.3
-10	10342	20684	48263	37921	139.7
-12	6895	13790	34474	24132	165.1
-16	8618	17237	34474	24132	187.5
-20	6895	13790	27579	20684	279.4
-24	6895	13790	27579	20684	355.6

TABLE III A - PERCENT OF SHIPMENT IN LENGTH RANGE SHOWN /4/

HOSE SIZE (REF)	3 TO 14FT. INCLUSIVE	OVER 14 FEET
-4 THRU -8	35%	65%
-10 THRU -16	45%	55%
-20 THRU -24	60%	40%

TABLE III B - PERCENT OF SHIPMENT IN LENGTH RANGE SHOWN (SI) /4/

HOSE SIZE (REF)	.91 TO 4.27 METERS INCLUSIVE	OVER 4.27 METERS
-4 THRU -8	35%	65%
-10 THRU -16	45%	55%
-20 THRU -24	60%	40%